

FIREKING 3-HOUR DATA SAFE



CAPACITY GUIDE

Media Type	DM1413-3	DM2513-3	DM2520-3	DM3420-3	DM4420-3
3.5" Diskettes					
Quantity per Drawer	306	306	536	536	536
Number of Fittings	3	6	6	8	10
3480 IBM Cartridges					
Quantity per Drawer	28	28	51	51	51
Number of Fittings	2	4	4	6	8
4mm DAT Tapes					
Quantity per Drawer	70	70	125	125	125
Number of Fittings	4	7	7	10	13
8mm DAT Tapes					
Quantity per Drawer	39	39	72	72	72
Number of Fittings	4	7	7	10	13
CD ROM					
Quantity per Drawer	70	70	123	123	123
Number of Fittings	2	4	4	5	7
DLT Tapes					
Quantity per Drawer	24	24	42	42	42
Number of Fittings	2	5	5	6	8
ZIP® PC 100					
Quantity per Drawer	73	73	128	128	128
Number of Fittings	3	5	5	7	9

Capacity guides are based on average media sizes.

TEST PROCEDURE

*Maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for class 125, when exposed to fire as per the Standard Time Temperature Curve for 3 hours to 1925°. Successfully undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test, the Humidity Test and the Fire and Impact Test.

OPTIONAL INTERIORS

- CM12-FS Fixed shelf for DM1413/DM2513
- CM12-CD Composite Drawer for DM1413/DM2513
- CM19-FS Fixed shelf for DM2520/DM3420/DM4420
- CM19-CD Composite Drawer for DM2520/DM3420/DM4420

SPECIFICATIONS

Model	Interior Size			Exterior Size			Weight	Capacity
	H	W	D	H	W	D		
DM1413-3	13 ⁵ / ₁₆ "	11 ¹ / ₂ "	16 ¹¹ / ₁₆ "	29 ⁹ / ₁₆ "	25 ¹ / ₄ "	31"	650 lbs.	1.5 cu. ft.
DM2513-3	24 ³ / ₁₆ "	11 ¹ / ₂ "	16 ¹¹ / ₁₆ "	40 ¹ / ₄ "	25 ¹ / ₄ "	31"	740 lbs.	2.7 cu. ft.
DM2520-3	24 ¹⁵ / ₁₆ "	18 ⁵ / ₁₆ "	16 ¹¹ / ₁₆ "	40 ¹ / ₄ "	32 ¹ / ₁₆ "	31"	1,050 lbs.	4.4 cu. ft.
DM3420-3	33 ¹ / ₁₆ "	18 ⁵ / ₁₆ "	16 ¹¹ / ₁₆ "	49 ⁹ / ₁₆ "	32 ¹ / ₁₆ "	31"	1,240 lbs.	6.0 cu. ft.
DM4420-3	43 ⁵ / ₁₆ "	18 ⁵ / ₁₆ "	16 ¹¹ / ₁₆ "	59 ³ / ₄ "	32 ¹ / ₁₆ "	31"	1,420 lbs.	7.9 cu. ft.

*Exterior depth does not include handle
Handle depth is 1 3/4"*

FIREKING 3-HOUR FIRE WITH IMPACT-RATED DATA SAFES

FIREKING 3-HOUR FIRE WITH IMPACT-RATED DATA SAFES

The FireKing 3-Hour Fire With Impact-Rated Data Safes provide the ultimate in protection against fire, dust, electrostatics and accidental damage for your computer media. They're our highest rated safes and are perfect for businesses with large-capacity electronic storage needs. FireKing 3-Hour Data Safes are available in five sizes, all featuring the UL Class 125 3-hour fire and impact rating*, plus the UL Residential Security Container (RSC) Burglary Rating for tough protection against break-in.

FEATURES

- Programmable electronic lock for security and easy access
- Safe is offered in our attractive Platinum finish
- UL RSC Burglary Rating
- UL Class 125 3-Hour fire and impact rating
- Canadian UL Class 52 3-Hour as to fire and impact resistance



www.uptime4u.com
UPTIME BUSINESS PRODUCTS
 800-222-1440